

TEGERA® 867

Synthetic glove, PU, palm-dipped, smooth finish, 13 gg, polyester, Cat. II, white, water and oil repellent palm, for fine assembly work

PROPERTIES

Flexible, breathable, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 13 gg, Polyester

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 260mm

COLOUR White

PAIRS PER PACKAGE/CARTON 6/120

DISPLAY Bulk pack OUTER MATERIAL SPECIFICATION
Polyurethane

INNER MATERIAL SPECIFICATION Polyester



SIZE	ART. NO.	EAN NO.
10	867-10	7392626072640
11	867-11	7392626072664
7	867-7	7392626072688
8	867-8	7392626072701
9	867-9	7392626072725
6	867-6	7392626075924

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 867

FEATURES

Water and oil repellent palm

PREVENTS RISK OF

Abrasion injuries, scratches, lacerations, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments, moist environments

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, electrical installation, fine assembly, glass industry work, HVAC installation, inspection work, installation work, machine operating, painting, shop work

PRIMARY INDUSTRIES OF USE

Automotive, transportation, utilities

TYPE OF WORK

Light weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 867

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com