



CRF[®]

SIZE	ART. NO.	EAN NO.
10	450-10	7392626073272
11	450-11	7392626073296
7	450-7	7392626073319
8	450-8	7392626073333
9	450-9	7392626073357
6	450-6	7340118310558

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA[®] 450

Cut resistant glove, nitrile, palm-dipped, foam grip pattern, cut resistance level C, 13 gg, CRF[®] Technology, glass fibre thread, nylon, polyester, spandex, Cat. II, black, water and oil repellent palm, for fine assembly work

PROPERTIES

High level of protection, durable, good grip

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 13,4

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile

LINING MATERIAL 13 gg, CRF[®] Technology, Glass fibre thread, Nylon, Polyester, Spandex

DEXTERITY 5

GRIP PATTERN Foam grip pattern

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 220 - 270mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot
OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE, glass fibre thread, polyester, nylon



TEGERA® 450

FEATURES

Cut resistant according to 388:2016 level C, oil and grease resistant

PREVENTS RISK OF

Cut injuries

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Assembly, engineering, inspection work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive

TYPE OF WORK

Light weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X44C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 450

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	4	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X44C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com