# **TEGERA®**



# MicroThan®+



SIZE	ART. NO.	EAN NO.
8	9161-8	7392626056343
9	9161-9	7392626056374
10	9161-10	7392626056404
11	9161-11	7392626056435
12	9161-12	7392626056466

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## **TEGERA® 9161**

Synthetic leather glove, half-lined, 0,7 mm Microthan®+, diamond grip pattern, polyester, bamboo, Cat. II, black, grey, reinforced seams, chrome free, elasticated 360°, for allround work

### **PROPERTIES**

Good fingertip sensitivity, flexible, very durable, excellent grip, perfect fit, extra comfortable

#### **SPECIFICATION**

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11, 12

COLLECTION PRO

PALM MATERIAL Microthan®+

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Half-lined

LINING MATERIAL Bamboo

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

FASTENING Elasticated 360°

LENGTH RANGE 225-265 mm

COLOUR Black, Grey

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

INNER MATERIAL SPECIFICATION Viscose

2021-01-10 www.ejendals.com

# **TEGERA®**



 $\epsilon$ 

Cat. II

EN 420:2003 + A1:2009







## **TEGERA® 9161**

#### **FEATURES**

Chrome free, reinforced index finger, reinforced seams, reinforced fingertips, specially designed thumb, windproof back, short model, ergonomically shaped, reflector, specially designed details

#### **PREVENTS RISK OF**

Chrome allergy, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with damp, contact with oil

#### **PRIMARY ENVIRONMENTS OF USE**

Dark environments, windy environments, slippery environments, dry environments, cold environments, moist environments, oily and greasy environments, dirty environments

#### **PRIMARY AREAS OF USE**

Agricultural work, airport work, assembly, building and construction, carpentry, concrete work, construction, engineering, forest work, gardening, HVAC installation, installation work, machine driving, machine operating, mining, soil preparation, transport work, warehouse work, wood industry work

### **PRIMARY INDUSTRIES OF USE**

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

#### TYPE OF WORK

Medium weight



**EJENDALS AB** 

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com

> > www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

# **TEGERA®**

# **TEGERA® 9161**

## **EU-TYPE EXAMINATION**

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

### **COMPLIANCE DESCRIPTION**

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

 $EN\,388{:}2016\,Protective\,gloves\,against\,mechanical\,risks$ 

Property	Level Achieved	(Maximum Performance)		
a) Resistance to abrasion (No. of revolutions)	2	(4)		
b) Cut resistance (Index)	1	(5)		
c) Tear resistance (N)	3	(4)		
d) Puncturing resistance (N)	1	(4)		
e) Cut resistance, EN ISO 13997 (N)	Х	(F)		
f) Impact protection, EN 13594:2015		(P)		

## EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	
d) Puncturing resistance (N)	20	60	1	00	00 150
Louis of muchanism (Danfarana Lauri		<u> </u>	<u> </u>		Τ.

Level of protection/Performance level	A	В	С	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	Р
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)






EN 420:2003 + A1:2009











Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10