



TEGERA® 722

Synthetic glove, nitrile, 3/4 dipped, smooth finish, 13 gg, polyester, Cat. II, white, yellow, water and oil repellent palm, for assembly work

PROPERTIES

Flexible, good fit, light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

DIPPING 3/4 dipped

DIPPING MATERIAL Nitrile

LINING MATERIAL 13 gg, Polyester

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 270mm

COLOUR White, Yellow

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Polyester

SIZE	ART. NO.	EAN NO.
6	722-6	7392626057883
7	722-7	7392626057890
8	722-8	7392626057906
9	722-9	7392626057913
10	722-10	7392626057920
11	722-11	7392626057937

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

**CE** Cat. IIEN 420:2003
+ A1:2009EN 388:2016
3121X

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

TEGERA® 722

FEATURES

Water and oil repellent palm and knuckle

PREVENTS RISK OF

Abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with oil, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Assembly, concrete work, construction, gardening, installation work, machine operating, sanitation, soil preparation, transport work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, machinery and equipment, MRO, automotive, transportation, utilities, building and construction

TYPE OF WORK

Medium weight

2(3)

ejendals
PROTECTING HANDS AND FEET**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 722

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com