



I N F I N I T Y TM



SIZE	ART. NO.	EAN NO.
7	8812-7	7340118321769
8	8812-8	7340118321783
9	8812-9	7340118321806
10	8812-10	7340118321721
11	8812-11	7340118321745

TEGERA® 8812 INFINITY

Cut resistant glove, nitrile, nitrile foam, waterbased PU, fully dipped, double-dipped, foam grip pattern, cut resistance level D, 15 gg, CRF® Technology, glass fibre thread, nylon, spandex, Cat. II, black, yellow, withstands contact heat up to 100°C, DMF (DMFa) free, oil and grease resistant, anatomically designed, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip in oily environments, extra comfortable

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level D

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 18,5

SIZE RANGE (EU) 7, 8, 9, 10, 11

COLLECTION Infinity

DIPPING Fully dipped, double-dipped

DIPPING MATERIAL Nitrile, nitrile foam, waterbased PU

LINING MATERIAL 15 gg, CRF® Technology, Glass fibre thread, Nylon, Spandex

DEXTERITY 5

GRIP PATTERN Foam grip pattern

CUFF STYLE Knitwrist cuff

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/120

PIECES PER BOX 0

DISPLAY Hook OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Glass fibre thread, HPPE, nylon, elastane

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X43D



EN 407:2004
X1XXXX



TEGERA® 8812 INFINITY

FEATURES

Cut resistant according to 388:2016 level D, withstands contact heat up to 100°C, approved for handling foodstuffs, oil and grease resistant, anatomically designed

PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Dry environments, wet environments, moist environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, engineering, fine assembly, glass industry work, HVAC installation, installation work, machine driving, machine operating, metalwork, paper industry work, repair work, service work, sheet-metal work, shop work, transport work, warehouse work

PRIMARY INDUSTRIES OF USE

Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

TEGERA® 8812 INFINITY

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	D	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X43D



EN 407:2004
X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com