

92-665

Disposable Nitrile Glove with Extended Cuff



Robust, extended cuff protection for food processing and heavy-duty jobs

- Superior chemical splash protection
- Extended cuff for protection of the wrist and forearm
- Soft, durable nitrile material for added comfort
- Textured fingertips provide secure grip
- Compliant with food handling requirements



Industries

- Life Sciences
- Chemical
- Food Processing

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Handling incoming goods
- Maintenance
- All food processing, applications that have food contact







92-665

Disposable Nitrile Glove with Extended Cuff

TECHNICAL DATA SHEET

PRODUCT INFORMATION

| | 92-665 |
|--------------------------------------|--|
| Material | Nitrile |
| Color | Blue |
| Glove Design | Chlorinated, Powder-Free, Silicone Free, Textured Fingers |
| Cuff | Beaded |
| Manufacturing/QMS Audit Standards | ISO 9001:2008 |
| Regulatory/Standards Compliance | ASTM D6319, Category III, EN ISO 374-1:2016, EN 374:2003, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600, ISO 9001 |
| Packaging | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country of Origin | Thailand |
| User Needs Segment | High Risk |
| Available sizes | S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10) |
| Sensitisers | Zinc Dibutyldithiocarbamate (ZDBC) Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions. |

PHYSICAL PROPERTIES

| | Typical | Typical Values | | |
|---|--------------|----------------|------------------|--|
| Length (mm/inches) | 300 | 300 / 11.8 | | |
| Freedom from Holes (Inspection level I) | 1.5 A | 1.5 AQL | | |
| Palm Thickness (mm/mils) | O.11 , | 0.11 / 4.3 | | |
| Finger Thickness (mm/mils) | 0.12 | 0.12 / 4.7 | | |
| | BEFORE AGING | AFTER AGING | | |
| Ultimate Tensile Strength (MPa) | ≥ 14 | ≥ 14 | ASTM D412 & D573 | |
| Elongation at Break (%) | ≥ 500 | ≥ 400 | ASTM D412 | |
| Force at break (N) | ≥ 6 | ≥ 6 | EN 455-2 | |

ORDERING INFORMATION

| Size | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|---------------------|-------------|-------------|-------------|---------------|
| Ansell Product Code | 92665070 | 92665080 | 92665090 | 92665100 |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC T: +1800 800 0444 F: +1800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia

Ansell PYC Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance











Ansell, $^{\odot}$ and $^{\odot}$ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking $^{\odot}$ 2020 Ansell Limited. All Rights Reserved.

